

Instanta SureFlow

Counter Top Boiler Chiller

Filtered boiling and chilled water

Features and benefits

- Adjustable boiling temperature programmable between 80°C - 98°C.
- Adjustable chilled temperature programmable between 3°C - 11°C.
- Provides filtered boiling and chilled water, meaning that there is no need to store and drink from expensive and environmentally damaging bottled water.
- AQ6 filter kit is included for fresh, pure-tasting water.
- Designed with non-drip taps for easy use.
- Complete with moulded plug.
- Stainless steel drip tray included.
- Dual safety protection against overfilling and boil dry to ensure user safety.
- Long-life Incoloy® elements to guarantee longevity.
- Compact and robust design, made to last.
- Installation is easy and convenient.

Filtration

The AQ6 filtration kit uses carbon block filters to remove impurities such as chlorine to improve the quality of boiling and chilled water.*

Temperature settings

- **Boiling:** factory set to operate at 96°C with an adjustable boiling temperature set-point.
- **Chilled:** programmable between 3°C - 11°C (subject to ambient temperatures).

Capacities

Boiling 28 litre, chilled 10 litre.

Power rating

3kW @ 230V.

Refrigerant

R290.

Construction

- Brushed stainless steel case.
- Stainless steel heating chamber.
- Low voltage switching.
- Two safety cut-outs.
- Mirror finish front panel.
- Well insulated for minimal heat loss and energy use.

Plumbing

Designed for a direct connection to a potable cold water supply with a minimum pressure of 2 bar. An isolating valve should be installed between the supply and the heater. Rear supply connection and choice of rear or front overflow.

Warranty

Two year warranty.

Installation

Easy to install on a worktop with integral drip tray. Should be sited in a well-ventilated area.

Electrical

Fitted with 1.75 metres of cable and a 13 amp moulded plug.

Product code	Capacity (litres)	Heat up time (minutes)	Power rating kW @ 230V	Rapid draw off (litres)	Boiling cups per hr @ 167ml	Chilled cups per hr @ 200ml	W x D x H (mm)
CTSBC2810	28 (boiling) 10 (chilled)	12	3	3	168	60 - 80	440 x 555 x 608

* AQ6 filtration kit should be changed every 6 months. Replacement product code: AQ6-FILTER.

