



Instanta SureFlow

Wall Mounted

Instant boiling water

Features and benefits

- Basic fault self-diagnostic system.
- Large heavy duty non-drip taps for ease of use.
- Insulation provides minimal heat loss, saving you money and energy.
- Dual safety protection against overfilling and boil dry, ensuring user safety.
- Mirror finished stainless steel case and long-life Incoloy® elements guarantee longevity.
- Easy access for service and cleaning guarantees convenience.

Capacities

2.5, 5 & 10 litre.

Power rating

- 2.5 litre: 2kW @ 230V.
- 5 & 10 litre: 3kW @ 230V.

Temperature settings

- Factory set to operate at 96°C.
- Adjustable boiling temperature set-point.

Construction

- Polished stainless steel case.
- Stainless steel heating chamber.
- Low voltage switching.
- Two safety cut outs.

Warranty

Two year warranty.

Installation

As per instruction manual supplied.

Plumbing

Designed for a direct connection to a potable cold water supply using the 15mm push-fit supplied. An isolating valve should be installed between the supply and the heater. These wall mounted boilers have a choice of connection through rear or from beneath and require two bar incoming water pressure.

Electrical

To be connected to a 230V, 13 amp supply.

| Product code | Capacity (litres) | Heat up time (minutes) | Power rating kW @ 230V | Rapid draw off (litres) | Boiling cups per hr @ 167ml | Tap depth (mm) | W x D x H (mm) |
|--------------|-------------------|------------------------|------------------------|-------------------------|-----------------------------|----------------|-----------------|
| WMS2 | 2.5 | 13 | 2 | 2.5 | 108 | 85 | 254 x 187 x 428 |
| WMS5 | 5 | 16 | 3 | 5 | 162 | 85 | 290 x 205 x 432 |
| WMS10 | 10 | 30 | 3 | 10 | 162 | 85 | 340 x 247 x 480 |