

Instanta SureFlow

Counter Top Compact

Boiling water from a compact unit

Features and benefits

- Compact counter top design to fit in areas with limited space, allowing instant access to high-quality boiling water.
- High-quality, heavy-duty draw-off tap and long-life Incoloy® elements guarantee longevity.
- Stainless steel drip tray included.
- Dual safety protection against overfilling and boil dry to ensure user safety.
- Easy install, service and cleaning access guarantees convenience and easy maintenance.
- Basic fault self-diagnosis to make sure your boiler is always performing to the highest standard.

Capacities

3 & 5 litre.

Power rating

- 3 litre: 2.25kW @ 230V.
- 5 litre: 3kW @ 230V.

Temperature settings

- Factory set to operate at 96°C.
- Adjustable boiling temperature set-point.

Warranty

Two year warranty.

Installation

Easy to install on a stable worktop.

Construction

- Brushed stainless steel case.
- Stainless steel heating chamber.
- Low voltage switching.
- Two safety cut-outs.
- Well insulated for minimal heat loss and energy use.

Plumbing

Designed for a direct connection to a potable cold water supply using the 1.5 metre (3/4" BSP) hose supplied. An isolating valve should be installed between the supply and the heater. Rear supply connection and choice of rear or front overflow is available (rear option requires kit not supplied).

Electrical

Fitted with 1.75 metres of cable and a 13 amp moulded plug.



Product code	Capacity (litres)	Heat up time (minutes)	Power rating kW @ 230V	Rapid draw off (litres)	Boiling cups per hr @ 167ml	W x D x H (mm)
CTS3	3	15	2.25	3	120	218 x 465 x 400
CTS5	5	16	3	5	162	218 x 465 x 440

Instanta SureFlow

Counter Top Boiler

Automatic-fill boiling water

Features and benefits

- High-quality, heavy-duty draw-off tap and long-life Incoloy® elements guarantee longevity.
- Stainless steel drip tray included.
- Dual safety protection against overfilling and boil dry to ensure user safety.
- Easy install, service and cleaning access guarantees convenience and easy maintenance.
- Basic fault self-diagnosis to make sure your boiler is always performing to the highest standard.
- Complete with 1.75 metres of cable and 13 amp plug.

Capacities

10 litre.

Power rating

3kW @ 230V.

Temperature settings

- Factory set to operate at 96°C.
- Adjustable boiling temperature set-point.

Warranty

Two year warranty.

Installation

Easy to install on a stable worktop.

Construction

- Mirror finished stainless steel case.
- Stainless steel heating chamber.
- Low voltage switching.
- Two safety cut-outs.
- Well insulated for minimal heat loss and energy use.

Plumbing

Designed for a direct connection to a potable cold water supply using the 1.5 metre (3/4" BSP) hose supplied. An isolating valve should be installed between the supply and the heater. Rear supply connection and choice of rear or front overflow is available (rear option requires kit not supplied).

Electrical

To be connected to a 230V supply with a suitable break capacity.

Product code	Capacity (litres)	Heat up time (minutes)	Power rating kW @ 230V	Rapid draw off (litres)	Boiling cups per hr @ 167ml	W x D x H (mm)
CTS10	10	32	3	10	168	243 x 510 x 610

