

Instanta SureFlow

Counter Top High Volume

High volume boiling water

Features and benefits

- Integral seven day programmable timer.*
- Energy saving ECO mode supports sustainability and cost reduction.*
- Adjustable temperature programmable between 80°C - 98°C.
- Comprehensive diagnostics system to make sure your boiler is always performing to the highest standard.
- Stainless steel drip tray included.*
- Dual safety protection against overflowing and boil dry to ensure user safety.
- Long-life Incoloy® elements to guarantee longevity.

Capacities

36, 50 & 135 litre.

Power rating

- 36 & 50 litre: 9kW @ 400V.
- 135 litre: 18kW @ 400V.

Temperature settings

- Factory set to operate at 96°C.
- Adjustable boiling temperature set-point.

Construction

- Brushed stainless steel case.
- Stainless steel heating chamber.

Taps

For situations where large volumes are required over a short timescale, the twin tap design speeds up delivery and halves serving time.

Warranty

Two year warranty.

Installation

Easy to install on a stable worktop.

Plumbing

The 36 & 50 litre models are designed for a direct connection to a potable cold water supply using the 1.5 metre (3/4" BSP) hose supplied. An isolating valve should be installed between the supply and the heater. Rear supply connection and choice of rear or front overflow.

The CTSV135T18 is designed for a direct connection to a potable cold water supply using the food quality hose supplied. An isolating valve should be installed between the supply and the heater. Rear connection and overflow. Requires 2 bar incoming water pressure.

Electrical

All models require a 400V, three phase supply.



Product code	Capacity (litres)	Heat up time (minutes)	Power rating kW @ 230V	Rapid draw off (litres)	Boiling cups per hr @ 167ml	W x D x H (mm)
CTSV36T9	36	23	9	30	500	440 x 555 x 608
CTSV50T9	50	35	9	50	500	440 x 555 x 760
CTSV135T18	135	44	18	135	1224	660 x 550 x 896

* Not available on the CTSV135T18.