

Instanta SureFlow Plus Wall Mounted

Instant boiling water

Features and benefits

- Electronic temperature control, programmable between 80°C - 98°C, ensuring every cup is delivered at the required temperature.
- Integral seven day programmable timer.
- Energy saving ECO mode supports sustainability and cost reduction.
- Comprehensive diagnostics system to make sure your boiler is always performing to the highest standard.
- Insulation provides minimal heat loss, saving you money and energy.
- Dual safety protection against overfilling and boil dry ensuring user safety.
- Easy install.
- Long-life Incoloy® elements guarantee longevity.

Capacities

3, 7, 15 & 25 litre.

Power rating

Please see table.

Temperature settings

- Factory set to operate at 96°C.
- Adjustable boiling temperature set-point between 80°C - 98°C.

Construction

- Stainless steel or impact resistant thermoplastic case.
- Stainless steel heating chamber.
- Low voltage switching.
- Two safety cut outs.

Warranty

Two year warranty.

Installation

As per instruction manual supplied.

Plumbing

Designed for a direct connection to a potable cold water supply using the fittings supplied. An isolating valve should be installed between the supply and the heater. These wall mounted boilers have a rear connection and overflow, requiring a 2 bar incoming water pressure.

Electrical

To be connected to a 230V, 13 amp or 30 amp (6kW) supply.



Product code	Capacity (litres)	Heat up time (minutes)	Power rating kW @ 230V	Rapid draw off (litres)	Boiling cups per hr @ 167ml	Tap depth (mm)	W x D x H (mm)
WMSP3W	3	11	3	3	168	90	332 x 210 x 452
WMSP3	3	11	3	3	168	90	314 x 215 x 414
WMSP7W	7	20	3	7	168	90	350 x 220 x 498
WMSP7	7	20	3	7	168	90	320 x 225 x 456
WMSP15	15	31	3	15	168	90	370 x 250 x 530
WMSP156	15	16	6	15	342	90	370 x 250 x 530
WMSP25	25	62	3	25	168	90	410 x 304 x 596
WMSP256	25	32	6	25	342	90	410 x 304 x 596